



gs flashing cement

1. description

gs flashing cement is a heavy bodied adhesive designed especially for vertical installations. Prepared from selected, blown asphalts, aliphatic solvents, non-asbestos fillers and reinforcing fibers. Available in winter, summer and Florida grade consistencies, to facilitate application during temperature extremes.

2. recommended uses

- a. Vertical details on BUR and modified bitumen membranes.
- b. Tie-offs at the end of the day's work, to repair bare spots, blisters, ruptures and splits.
- c. Can be used to seal around skylights, vent pipes or other roof top projections.

3. benefits

- a. Resistant to chemical and ultraviolet attack.
- b. Resists flow at high roof top temperatures.
- c. Climate formulated for year round applications.
- d. Meets current VOC requirements.
- e. Non-Asbestos.
- f. Cold applied with a trowel and cures to a tough, durable protective barrier.
- g. ASTM D4586, D3409, UL Classified.

4. physical features

property	typical value	Test method
weight / gallon, lbs.	8.3 – 8.7	D6511
solids, % by weight	48 - 52	D6511
solids, % by volume	48 - 52	
viscosity, cps	6500 - 10000	Brookfield, RVT
pH	6.2 – 7.2	
flash point, ° F	none	PMCC
color, cured	black	visual
drying time, touch	1-2 hours	70 ° F / 50% RH
shelf life	1 year	70 ° F / 50% RH
VOC	zero	EPA method 24A